

MOTIP Wheel Protect Wax

Technical Information



Protect your rims and hubcaps with MOTIP Wheel Protect Wax. Wheel Protect Wax gives a glossy result, reduces the adhesion of dirt, is free from solvents, is pH-neutral and contains silicones.

Ord.-no: 000733

Quality & properties

- Reduces the adhesion of dirt
- Gives a glossy result
- Free from solvents
- pH-neutral
- Contains silicones
- User-friendly

Physical & chemical data

- Base: PE Wax
- Colourname: white
- Surfaces: Rims, hubcaps
- Minimum Working Temperature: 10 °C
- Maximum Working Temperature: 25 °C
- Flash point: 100 °C
- Storage stability: 10 y
- Content: 500 ML

How to use

Before use, carefully read the directions on the packaging and act accordingly. Store frost-free.
The surface should be clean and dry.
When desired, clean the rims or the hubcaps with MOTIP Wheel Cleaner.
Apply Wheel Protect Wax in a thin, equal layer and polish with a soft cloth.

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of May 7, 2025 – This release replaces all eventually earlier issued versions.