

MOTIP Food Grade - Chain Oil

Technical Information



Lubricant to treat chain-driven transmissions, which are liable to heavy load. In view of the unique formula, suitable for use in the food industry, in accordance with NSF registration H1 number, 139848. Chain oil can be processed like oil, with the properties of grease.

Ord.-no: 005060

Quality & properties

- NSF registration H1, number 139848
- To be processed like oil, with the properties of grease
- Outstanding mechanical and thermal stability
- Good adhesion
- Dilatant
- Prevents wear and sticking
- Resistant to weather influences
- Resistant to weak acids and bases
- Water-repellent
- 360° valve

Physical & chemical data

- Base: Mineral oil
- Colourname: no colour
- Surfaces: Chains, Chain driven transmissions liable to heavy load, Conveyors
- Flash point: n.a.
- Content: 500 ML

How to use

- Before use, carefully read the directions on the packaging and act accordingly.
- The aerosol should have room temperature.
- Best processing temperature 10 to 25°C.
- Before use, shake the aerosol.
- Apply the chain oil in a thin layer. During the initial flow phase, when the product can really penetrate the treated chain, the spray has a foaming effect.

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of August 4, 2025 – This release replaces all eventually earlier issued versions.