

MOTIP Food Grade - Machine Oil

Technical Information



Lubrication and preservative for machine parts with excellent penetrating properties. Extremely suitable as a tool to loosen rusted machine parts. In view of the unique formula, suitable for use in the food industry, in accordance with NSF registration H1, number 139847.

Ord.-no: 005040

Quality & properties

- NSF registration H1, number 139847
- Outstanding mechanical and thermal stability
- Excellent penetrating properties
- Moisture repellent
- Corrosion preventive
- Free from solvents
- Directed jetspray
- 360° valve

Physical & chemical data

- Base: Paraffin oil
- Colourname: no colour
- Surfaces: Chains, Bearings, Screwed connections, Valves, Gear Wheels, Pistons, Filters, Fasteners (screws bolts and nuts)
- Flash point: n.a.
- Content: 500 ML

How to use

- Before use, carefully read the directions on the packaging and act accordingly.
- The aerosol should have room temperature.
- Best processing temperature 10 to 25°C.
- Before use, shake the aerosol.
- Apply machine oil and allow to take effect.

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of August 4, 2025 – This release replaces all eventually earlier issued versions.