

MOTIP Food Grade - Spray Grease

Technical Information



Spray grease with PTFE to treat metal or plastic mechanical parts. In view of the high viscosity, extremely suitable for lubricating parts, which are liable to heavy pressure. In view of the unique formula, suitable for use in the food industry, in accordance with NSF registration H1, number 139849.

Ord.-no: 005070

Quality & properties

- NSF registration H1, number 139849
- Outstanding mechanical and thermal stability
- Excellent adhesion
- Prevents wear and sticking
- High viscosity
- Resistant to weather influences
- Resistant to weak acids and bases
- Excellent corrosion prevention
- Contains PTFE (polytetrafluorethen)
- 360° valve

Physical & chemical data

- Base: EP-2 Grease with PTFE
- Colourname: no colour
- Smell: Characteristic
- Surfaces: Metal to metal connections, Bearings, Metal to plastic connections, Door hinges, Springs, Stabilization rubbers, Worm wheels, Conveyors
- Flash point: n.a.
- Content: 500 ML

How to use

- Before use, carefully read the directions on the packaging and act accordingly.
- The aerosol should have room temperature. Best processing temperature 10 to 25°C.
- Before use, shake the aerosol.
- Apply the spray grease in a thin layer.

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of August 4, 2025 – This release replaces all eventually earlier issued versions.