

MOTIP Food Grade - Ultra Oil

Technical Information



Universal oil with PTFE to lubricate and protect metal and plastic parts. In view of the unique formula, suitable for use in the food industry, in accordance with NSF registration H1, number 139850.

Ord.-no: 005050

Quality & properties

NSF registration H1, number 139850
Good penetrating properties
Water and moisture repellent
Corrosion preventive
Directed jetspray
360° valve

Physical & chemical data

Base: Synthetic oil with additives
Colourname: no colour
Surfaces: Chains, Machinery, Motions, Fasteners (screws, bolts and nuts), Tools, Conveyors, Skeelers, Skates, Skateboards
Flash point: n.a.
Content: 500 ML

How to use

Before use, carefully read the directions on the packaging and act accordingly.
The aerosol should have room temperature.
Best processing temperature 10 to 25°C.
Before use, shake the aerosol.
Apply Ultra Oil in the desired quantity.
As a result of the unique formula a protecting film is formed.

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of August 4, 2025 – This release replaces all eventually earlier issued versions.