

MOTIP Backlight Paint

Technical Information



Highlight the rear lights of your car with MOTIP Backlight Spray. The transparent lacquer has a lasting gloss and is scratch-free and shock proof. The lacquer is resistant to petrol, chemicals and the weather.

Ord.-no: 00260, 00261, 00160, 00161, 880112

Quality & properties

Not suitable to treat surfaces of polycarbonate!
Lasting gloss
Scratch free and shock proof
Resistant to petrol, chemicals and weather influences
Good adhesion

Physical & chemical data

Base: Alkyd resin
Colourname:

- black
- red
- orange

Smell: Characteristic
Degree of gloss: gloss, >75
Efficiency:

- 400 ML – 8 backlights
- 150 ML – 2 to 4 backlights m²

Dust dry: 10 - 20 min
Dry to touch: 60 min
Completely dry: 4 h
Overcoatable: 4 min
Surfaces: Backlights
Minimum Working Temperature:

- 10 °C
- 10

Maximum Working Temperature:

- 25 °C
- 25

Flash point:

- n.a.
- n.a. °C

Storage stability: 10 years
Content:

- 400 ML
- 150 ML

How to use

Before use, carefully read the directions on the packaging and act accordingly.

The surface must be clean, dry and free of grease.

The aerosol should have room temperature. Best processing temperature 10 to 25°C.

Before use, shake the aerosol for 2 minutes and spray a sample. Distance to the surface to be treated approximately 25 to 30 centimetre.

Spray the lacquer in several thin layers, till the desired result has been achieved. (Before applying the next layer, again shake the aerosol).

After use, clean the valve (turn aerosol upside down and press the nozzle for approximately 5 seconds).

The drying time depends on the ambient temperature, the humidity of the air and the thickness of the lacquer applied.

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of August 4, 2025 – This release replaces all eventually earlier issued versions.